



NOTES:

AGGREGATE SIZE - USE 2-3 INCH WASHED STONE, WITH GEO-TEX LINER

DIMENSIONS OF GRAVEL PAD:

THICKNESS = 8 INCHES MINIMUM

WIDTH = 25 FOOT MINIMUM OF FULL WIDTH AT ALL POINTS OF THE VEHICULAR ENTRANCE AND EXIT AREA, WHICHEVER IS GREATER

LENGTH = 100 FOOT MINIMUM WITH GEO-TEX LINER

LOCATION = LOCATE CONSTRUCTION ENTRANCES AND EXITS TO LIMIT SEDIMENT FROM LEAVING THE SITE AND TO PROVIDE FOR MAXIMUM UTILITY BY ALL CONSTRUCTION VEHICLES. AVOID STEEP GRADES AND ENTRANCES AT CURVES IN PUBLIC ROADS.

SITE CONDITIONS MAY REQUIRE VARIATIONS FROM THESE DESIGN CRITERIA. VARIATIONS WILL BE DETERMINED OR APPROVED BY EITHER THE APPROPRIATE CITY OR STATE EROSION CONTROL AUTHORITY.

DATE: 3/1/14

CITY OF REIDSVILLE

TEMPORARY CONSTRUCTION ENTRANCE DETAIL

STD. NO.

REV.

217